N-Channel Enhancement Mode MOSFET


Features

- 30V/12A,
  $R_{DS(ON)}$ = 9mΩ (typ.) @ V_{GS} = 10V
  $R_{DS(ON)}$ =12mΩ (typ.) @ V_{GS} = 4.5V
- Super High Dense Cell Design
- Reliable and Rugged
- SOP-8 Package
- Lead Free Available (RoHS Compliant)


Applications

- Power Management in Notebook Computer, Portable Equipment and Battery Powered Systems

Pin Description



Top View of SOP – 8



N-Channel MOSFET

Ordering and Marking Information

APM4412 □□-□□ □

- Lead Free Code
- Handling Code
- Temp. Range
- Package Code

Package Code
K : SOP-8
Operating Junction Temp. Range
C : -55 to 150°C
Handling Code
TU : Tube TR : Tape & Reel
Lead Free Code
L : Lead Free Device Blank : Original Device

APM4412 K : APM4412 XXXXX

XXXXX - Date Code

Note: ANPEC lead-free products contain molding compounds/die attach materials and 100% matte tin plate termination finish; which are fully compliant with RoHS and compatible with both SnPb and lead-free soldiering operations. ANPEC lead-free products meet or exceed the lead-free requirements of IPC/JEDEC J STD-020C for MSL classification at lead-free peak reflow temperature.

ANPEC reserves the right to make changes to improve reliability or manufacturability without notice, and advise customers to obtain the latest version of relevant information to verify before placing orders.

Downloaded from Elcodis.com electronic components distributor

Absolute Maximum Ratings (T_A = 25°C unless otherwise noted)

Symbol	Parameter		Rating	Unit
V_{DSS}	Drain-Source Voltage		30	V
V_{GSS}	Gate-Source Voltage		±20	
I_D*	Continuous Drain Current	V_{GS}=10V	12	A
I_{DM}*	300µs Pulsed Drain Current		45	
I_S*	Diode Continuous Forward Current		2	A
T_J	Maximum Junction Temperature		150	°C
T_{STG}	Storage Temperature Range		-55 to 150	
P_D*	Maximum Power Dissipation	T_A=25°C	2	W
		T_A=100°C	0.8	
$R_{\theta JA}$*	Thermal Resistance-Junction to Ambient		62.5	°C/W

Note:

*Surface Mounted on 1in^2 pad area, t ≤ 10sec.

Electrical Characteristics (T_A = 25°C unless otherwise noted)

Symbol	Parameter	Test Condition	APM4412K			Unit
			Min.	Typ.	Max.	
Static Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS}=0V, I_{DS}=250µA	30			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=24V, V_{GS}=0V			1	µA
		T_J=85°C			30	
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_{DS}=250µA	1.3	1.7	2.5	V
I_{GSS}	Gate Leakage Current	V_{GS}=±20V, V_{DS}=0V			±100	nA
$R_{DS(ON)}$ [a]	Drain-Source On-state Resistance	V_{GS}=10V, I_{DS}=12A		9	12	mΩ
		V_{GS}=4.5V, I_{DS}=8A		12	16	
V_{SD} [a]	Diode Forward Voltage	I_{SD}=2.3A, V_{GS}=0V		0.75	1.3	V
Gate Charge Characteristics [b]						
Q_g	Total Gate Charge	V_{DS}=15V, V_{GS}=10V, I_{DS}=12A		24.5	32	nC
Q_{gs}	Gate-Source Charge			4		
Q_{gd}	Gate-Drain Charge			8		

Copyright © ANPEC Electronics Corp.

Downloaded from Elcodis.com electronic components distributor

Electrical Characteristics (Cont.) (T_A = 25°C unless otherwise noted)

Symbol	Parameter	Test Condition	APM4412K			Unit
			Min.	Typ.	Max.	
Dynamic Characteristics[b]						
R_G	Gate Resistance	V_{GS}=0V,V_{DS}=0V,F=1MHz		2.3		Ω
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=25V, Frequency=1.0MHz		1470		pF
C_{oss}	Output Capacitance			233		
C_{rss}	Reverse Transfer Capacitance			157		
$t_{d(ON)}$	Turn-on Delay Time	V_{DD}=15V, R_L=15Ω, I_{DS}=1A, V_{GEN}=10V, R_G=6Ω		13	24	ns
T_r	Turn-on Rise Time			9	17	
$t_{d(OFF)}$	Turn-off Delay Time			36	66	
T_f	Turn-off Fall Time			12	23	
t_{rr}	Reverse Recovery Time	I_{SD}=12A, dI_{SD}/dt =100A/µs		14		ns
Q_{rr}	Reverse Recovery Charge			5		nC

Notes:


a : Pulse test ; pulse width≤300µs, duty cycle≤2%.

b : Guaranteed by design, not subject to production testing.


Downloaded from Elcodis.com electronic components distributor

Typical Characteristics


Power Dissipation




Drain Current



Safe Operation Area




Thermal Transient Impedance




Downloaded from Elcodis.com electronic components distributor

Typical Characteristics (Cont.)


Output Characteristics




Drain-Source On Resistance



Transfer Characteristics




Gate Threshold Voltage




Downloaded from Elcodis.com electronic components distributor

Typical Characteristics (Cont.)


Drain-Source On Resistance




Source-Drain Diode Forward



Capacitance




Gate Charge



Downloaded from Elcodis.com electronic components distributor

Packaging Information

SOP-8 pin (Reference JEDEC Registration MS-012)




Dim	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	1.35	1.75	0.053	0.069
A1	0.10	0.25	0.004	0.010
D	4.80	5.00	0.189	0.197
E	3.80	4.00	0.150	0.157
H	5.80	6.20	0.228	0.244
L	0.40	1.27	0.016	0.050
e1	0.33	0.51	0.013	0.020
e2	1.27BSC		0.50BSC	
ϕ 1	8°		8°	

Downloaded from Elcodis.com electronic components distributor

Physical Specifications

Terminal Material	Solder-Plated Copper (Solder Material : 90/10 or 63/37 SnPb), 100%Sn
Lead Solderability	Meets EIA Specification RSI86-91, ANSI/J-STD-002 Category 3.

Reflow Condition (IR/Convection or VPR Reflow)



Classification Reflow Profiles

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Average ramp-up rate (T_L to T_P)	3°C/second max.	3°C/second max.
Preheat - Temperature Min (Tsmin) - Temperature Max (Tsmax) - Time (min to max) (ts)	100°C 150°C 60-120 seconds	150°C 200°C 60-180 seconds
Time maintained above: - Temperature (T_L) - Time (t_L)	183°C 60-150 seconds	217°C 60-150 seconds
Peak/Classificatioon Temperature (Tp)	See table 1	See table 2
Time within 5°C of actual Peak Temperature (tp)	10-30 seconds	20-40 seconds
Ramp-down Rate	6°C/second max.	6°C/second max.
Time 25°C to Peak Temperature	6 minutes max.	8 minutes max.

Notes: All temperatures refer to topside of the package .Measured on the body surface.

Copyright © ANPEC Electronics Corp.

Downloaded from Elcodis.com electronic components distributor

Classification Reflow Profiles(Cont.)

Table 1. SnPb Entectic Process – Package Peak Reflow Temperatures

Package Thickness	Volume mm^3 <350	Volume mm^3 ³350
<2.5 mm	240 +0/-5°C	225 +0/-5°C
≥2.5 mm	225 +0/-5°C	225 +0/-5°C

Table 2. Pb-free Process – Package Classification Reflow Temperatures


Package Thickness	Volume mm^3 <350	Volume mm^3 350-2000	Volume mm^3 >2000
<1.6 mm	260 +0°C*	260 +0°C*	260 +0°C*
1.6 mm – 2.5 mm	260 +0°C*	250 +0°C*	245 +0°C*
≥2.5 mm	250 +0°C*	245 +0°C*	245 +0°C*

*Tolerance: The device manufacturer/supplier **shall** assure process compatibility up to and including the stated classification temperature (this means Peak reflow temperature +0°C. For example 260°C+0°C) at the rated MSL level.

Reliability Test Program


Test item	Method	Description
SOLDERABILITY	MIL-STD-883D-2003	245°C,5 SEC
HOLT	MIL-STD 883D-1005.7	1000 Hrs Bias @ 125°C
PCT	JESD-22-B, A102	168 Hrs, 100% RH, 121°C
TST	MIL-STD 883D-1011.9	-65°C ~ 150°C, 200 Cycles

Carrier Tape & Reel Dimensions



Downloaded from Elcodis.com electronic components distributor

Carrier Tape & Reel Dimensions(Cont.)



Application	A	B	C	J	T1	T2	W	P	E
SOP-8	330±1	62 ± 1.5	12.75 + 0.1 5	2 + 0.5	12.4 +0.2	2± 0.2	12 + 0.3 - 0.1	8± 0.1	1.75± 0.1
	F	D	D1	Po	P1	Ao	Bo	Ko	t
	5.5 ± 0.1	1.55±0.1	1.55+ 0.25	4.0 ± 0.1	2.0 ± 0.1	6.4 ± 0.1	5.2± 0.1	2.1± 0.1	0.3±0.013

(mm)

Cover Tape Dimensions

Application	Carrier Width	Cover Tape Width	Devices Per Reel
SOP- 8	12	9.3	2500

Customer Service

Anpec Electronics Corp.

Head Office :

No.6, Dusing 1st Road, SBIP,

Hsin-Chu, Taiwan, R.O.C.

Tel : 886-3-5642000

Fax : 886-3-5642050

Taipei Branch :

7F, No. 137, Lane 235, Pac Chiao Rd.,

Hsin Tien City, Taipei Hsien, Taiwan, R. O. C.

Tel : 886-2-89191368

Fax : 886-2-89191369

Downloaded from Elcodis.com electronic components distributor