Ordering number : ENA0775

SANYO Semiconductors

DATA SHEET

N-Channel Silicon MOSFET

2SK4097LS — General-Purpose Switching Device Applications

Features

- Low ON-resistance, low input capacitance, ultrahigh-speed switching.
- Adoption of high reliability HVP process.
- Attachment workability is good by Mica-less package.
- Avalanche resistance guarantee.

Specifications

Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Conditions	Ratings	Unit
Drain-to-Source Voltage	V_{DSS}		500	V
Gate-to-Source Voltage	V_{GSS}		±30	V
Drain Current (DC)	I_{Dc}*1	Limited only by maximum temperature	9.5	A
	I_{Dpack}*2	SANYO's ideal heat dissipation condition	8.3	A
Drain Current (Pulse)	I_{DP}	PW≤10μs, duty cycle≤1%	38	A
Allowable Power Dissipation	P_D		2.0	W
		Tc=25°C (SANYO's ideal heat dissipation condition)	35	W
Channel Temperature	Tch		150	°C
Storage Temperature	Tstg		–55 to +150	°C
Avalanche Energy (Single Pulse) *3	E_{AS}		280	mJ
Avalanche Current *4	I_{AV}		9.5	A

*1 Shows chip capability

*2 Package limited

*3 V_{DD}=99V, L=5mH, I_{AV}=9.5A

*4 L≤5mH, single pulse

Marking : K4097

■ Any and all SANYO Semiconductor Co.,Ltd. products described or contained herein are, with regard to "standard application", intended for the use as general electronics equipment (home appliances, AV equipment, communication device, office equipment, industrial equipment etc.). The products mentioned herein shall not be intended for use for any "special application" (medical equipment whose purpose is to sustain life, aerospace instrument, nuclear control device, burning appliances, transportation machine, traffic signal system, safety equipment etc.) that shall require extremely high level of reliability and can directly threaten human lives in case of failure or malfunction of the product or may cause harm to human bodies, nor shall they grant any guarantee thereof. If you should intend to use our products for applications outside the standard applications of our customer who is considering such use and/or outside the scope of our intended standard applications, please consult with us prior to the intended use. If there is no consultation or inquiry before the intended use, our customer shall be solely responsible for the use.

■ Specifications of any and all SANYO Semiconductor Co.,Ltd. products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

SANYO Semiconductor Co., Ltd.

TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110-8534 JAPAN


Electrical Characteristics at Ta=25°C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Drain-to-Source Breakdown Voltage	$V_{(BR)DSS}$	I_D=10mA, V_{GS}=0V	500			V
Zero-Gate Voltage Drain Current	I_{DSS}	V_{DS}=400V, V_{GS}=0V			100	μA
Gate-to-Source Leakage Current	I_{GSS}	V_{GS}=±30V, V_{DS}=0V			±100	nA
Cutoff Voltage	$V_{GS}(off)$	V_{DS}=10V, I_D=1mA	3		5	V
Forward Transfer Admittance	$\|yfs\|$	V_{DS}=10V, I_D=5A	3	6		S
Static Drain-to-Source On-State Resistance	$R_{DS}(on)$	I_D=5A, V_{GS}=10V		0.5	0.65	Ω
Input Capacitance	Ciss	V_{DS}=30V, f=1MHz		750		pF
Output Capacitance	Coss	V_{DS}=30V, f=1MHz		150		pF
Reverse Transfer Capacitance	Crss	V_{DS}=30V, f=1MHz		35		pF
Turn-ON Delay Time	$t_d(on)$	See specified Test Circuit.		16		ns
Rise Time	t_r	See specified Test Circuit.		44		ns
Turn-OFF Delay Time	$t_d(off)$	See specified Test Circuit.		102		ns
Fall Time	t_f	See specified Test Circuit.		47		ns
Total Gate Charge	Qg	V_{DS}=200V, V_{GS}=10V, I_D=9.5A		30		nC
Gate-to-Source Charge	Qgs	V_{DS}=200V, V_{GS}=10V, I_D=9.5A		5.2		nC
Gate-to-Drain “Miller” Charge	Qgd	V_{DS}=200V, V_{GS}=10V, I_D=9.5A		17		nC
Diode Forward Voltage	V_{SD}	I_S=9.5A, V_{GS}=0V		0.9	1.2	V


Package Dimensions

unit : mm (typ)


7509-002





Switching Time Test Circuit





Avalanche Resistance Test Circuit






ID – VDS
Tc=25°C
15V
10V
8V
6V
VGS=5V
Drain Current, ID – A
Drain-to-Source Voltage, VDS – V
IT12372



ID – VGS
VDS=20V
Tc= –25°C
25°C
75°C
Drain Current, ID – A
Gate-to-Source Voltage, VGS – V
IT12373



RDS(on) – VGS
ID=5A
Tc=75°C
25°C
–25°C
Static Drain-to-Source On-State Resistance, RDS(on) – Ω
Gate-to-Source Voltage, VGS – V
IT12374



RDS(on) – Tc
VGS=10V, ID=5A
Static Drain-to-Source On-State Resistance, RDS(on) – Ω
Case Temperature, Tc – °C
IT12375



|yfs| – ID
VDS=10V
25°C
Tc= –25°C
75°C
Forward Transfer Admittance, |yfs| – S
Drain Current, ID – A
IT12376



IS – VSD
VGS=0V
Tc=75°C
25°C
–25°C
Source Current, IS – A
Diode Forward Voltage, VSD – V
IT12377



SW Time – ID
VDD=200V
VGS=10V
td(off)
tf
tr
td(on)
Switching Time, SW Time – ns
Drain Current, ID – A
IT12378



Ciss, Coss, Crss – VDS
f=1MHz
Ciss
Coss
Crss
Ciss, Coss, Crss – pF
Drain-to-Source Voltage, VDS – V
IT12379


VGS – Qg
VDS=200V
ID=9.5A
Gate-to-Source Voltage, VGS – V
Total Gate Charge, Qg – nC
IT12380


A S O
IDP=38A
PW≤10μs
10μs
100μs
1ms
10ms
100ms
DC operation
IDC(*1)=9.5A
IDpack(*2)=8.3A
Operation in this area is limited by RDS(on).
Tc=25°C
Single pulse
*1. Shows chip capability
*2. SANYO's ideal heat dissipation condition
Drain Current, ID – A
Drain-to-Source Voltage, VDS – V
IT12381


PD – Ta
Allowable Power Dissipation, PD – W
Ambient Temperature, Ta – °C
IT12337


PD – Tc
Allowable Power Dissipation, PD – W
Case Temperature, Tc – °C
IT12382


EAS – Ta
Avalanche Energy derating factor – %
Ambient Temperature, Ta – °C
IT10478

Note on usage : Since the 2SK4097LS is a MOSFET product, please avoid using this device in the vicinity of highly charged objects.

- SANYO Semiconductor Co.,Ltd. assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all SANYO Semiconductor Co.,Ltd. products described or contained herein.
- SANYO Semiconductor Co.,Ltd. strives to supply high-quality high-reliability products, however, any and all semiconductor products fail or malfunction with some probability. It is possible that these probabilistic failures or malfunction could give rise to accidents or events that could endanger human lives, trouble that could give rise to smoke or fire, or accidents that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all SANYO Semiconductor Co.,Ltd. products described or contained herein are controlled under any of applicable local export control laws and regulations, such products may require the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written consent of SANYO Semiconductor Co.,Ltd.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO Semiconductor Co.,Ltd. product that you intend to use.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production.
- Upon using the technical information or products described herein, neither warranty nor license shall be granted with regard to intellectual property rights or any other rights of SANYO Semiconductor Co.,Ltd. or any third party. SANYO Semiconductor Co.,Ltd. shall not be liable for any claim or suits with regard to a third party's intellctual property rights which has resulted from the use of the technical information and products mentioned above.

This catalog provides information as of June, 2007. Specifications and information herein are subject to change without notice.